

ProfiLine Portable DO-Meter Oxi 1970i, WTW

ProfiLine portable DO-meter Oxi 1970i

Extremely robust and submersible (IP 67) instrument for field measurements of dissolved oxygen with connection for depth fittings with up to 100 m cable. Integrated rechargeable battery, operation also with wide-band mains power supply unit (included with delivery). AutoRead ensures reliable results. With memory for 800 entries, data logger, real-time clock and GLP-supporting functions. Complete with bidirectional RS 232 interface.

Technical data:

Saturation:	0.0 to 199.9% 0 to 600%
Concentration:	0.00 to 19.99 mg/l 0 to 90 mg/l
Temperature:	-5.0 to 50.0°C
Accuracy:	O ₂ ±0.5 % of measured value Temp. ±0.1 K

Article	Order No.
Oxygen meter ProfiLine Oxi 1970i	61 81 23110

Accessories

Article	Order No.
Oxygen sensor CelloX® 325	68 81 32533
Galvanic dissolved oxygen sensor with water-proof connector, cable length 1.5 m	
Oxygen depth sensor TA 197 Oxi-25	68 81 32534
Oxygen depth sensor with integrated temperature sensor and 25 m cable (optionally up to 100 m) with water-proof connector (IP67), pressure-proof steel case and screw-off protective hood, fits 2" bore holes	
NT multirange wide-band power supply unit	61 81 02867

