

Safety Underbench Cabinets, asecos

Suitable for placement under fume hoods.

Proper storage of hazardous substances in work areas in compliance with TRbF 20 Appendix L (German Flammable Liquids Regulations).

Type-tested to withstand fire for 90 minutes as defined in EN 14470-1 (Type 90).

Expansion joints provide protection in case of fire. Fine sheet steel outer shell with plastic coating, light gray (RAL 7035). Plastic coating with good chemical, impact and scratch resistance characteristics applied to inner surface. Edge protection on insulation material. External ground connection.

Mopel VBF.60.110-S

- one fully extendable drawer, can be locked in any position
- useable internal height (without perforated insert): 415 mm

Standard equipment:

- integrated pull-out pan
- open drawer closes in case of fire (thermal activation)
- Ground cable with clamp in the drawer.

Technical data:

External dimensions (W × D × H):	approx. 1100 × 570 × 600 mm
Drawer (W × D × H):	approx. 930 × 442 × 80 mm
Drawer load capacity (distributed load):	50 kg



①



②

Article	Order No.
① VBF.60.110-S with pull-out pan	91 13 56011

Delivery costs depending on place of delivery

Interior equipment versions model VBF.60.110-S

Article	Order No.
Perforated plate insert (stainless steel 1.4301)	91 13 19973
2nd drawer level (powder-coated steel plate)	91 13 18053
Base (powder-coated steel plate) H 30 mm	91 13 17212
Base (powder-coated steel plate) H 65 mm	91 13 17213

Mopel VBF.60.110-T

- 2 wing doors
- useable internal height (without perforated insert and shelf) 440 mm

External dimensions (W × D × H): approx. 1100 × 570 × 600 mm

Article	Order No.
② Model VBF.60.110-T (without interior)	91 13 66011

Delivery costs depending on place of delivery

Interior equipment versions model VBF.60.110-T

Recommended configuration: perforated plate insert and bottom collecting pan

Article	W × D × H mm	Order No.
Shelf	970×415×20	91 13 18376
Perforated plate insert	975×440×70	91 13 18374
Bottom collecting pan	975×442×70	91 13 18372
Base (powder-coated steel plate) H 30 mm		91 13 17212
Base (powder-coated steel plate) H 65 mm		91 13 17213

The underbench cabinets can be installed without a base.