

BOLA Distributors for Bottles, Bohlender

Black screw cap made of PPS for bottle thread GL 45. Without stopcocks: body made of PTFE with 2 or 4 ports with female thread UNF 1/4" 28G on upper and lower sides. With stopcocks: body made of PTFE with 2 or 3 ports with female thread UNF 1/4" 28G on upper and lower sides and stopcock made of FEP for each port. A possible unevenness of the bottle neck is adjusted by an o-ring behind an elastic sealing lip, and the bottle is closed tightly. The product is only exposed to the body of the distributor. The body of the distributor can be turned independently from the screw cap. This means, that the assembled distributor can be removed completely and fixed on another bottle without the risk of disarranging the tubing. Very good chemical resistance, for working temperatures up to +200°C.

Applications: HPLC

Technical data:

Material: PTFE, PPS
 Temperature resistance: from -15°C to +200°C
 Chemical resistance: +++ universal

	for tubing inner Ø x outer Ø mm	Quantity stop- cocks	Through bore mm	Connection	Order No.
①	0.8 x 1.6	–	0.8	2 x UNF 1/4" 28G	10 17 64502
①	1.6 x 3.2	–	1.6	2 x UNF 1/4" 28G	10 17 64504
②	0.8 x 1.6	–	0.8	4 x UNF 1/4" 28G	10 17 64510
②	1.6 x 3.2	–	1.6	4 x UNF 1/4" 28G	10 17 64512
③	0.8 x 1.6	2	0.8	2 x UNF 1/4" 28G	10 17 64602
③	1.6 x 3.2	2	1.6	2 x UNF 1/4" 28G	10 17 64604
④	0.8 x 1.6	3	0.8	3 x UNF 1/4" 28G	10 17 64611
④	1.6 x 3.2	3	1.6	3 x UNF 1/4" 28G	10 17 64612

