

SICCO Mini 1 Premium Desiccators, Bohlender

These desiccators are designed to keep small parts susceptible to humidity dry in a safe, protected, and dust-free environment. This goal is achieved by the addition of silica gel. The desiccator is sealed by a circumferential rubber gasket. The handy-sized Mini units have non-slip rubber feet and are easy to stack.

The integrated digital hygrometer is easy to read; it is comprised in the delivery as a standard, just as two intermediate shelves made of PMMA and a small jar of silica gel.

Technical data:

Capacity:	6.2 l
Weight:	0.9 kg
Total all-over load:	3 kg
Pressure load:	normal pressure
Temperature resistance:	-35°C to +70°C

Outer dimensions (W×H×D): 221 × 183 × 214 mm

Usable interior space (W×H×D): 212 × 162 × 180 mm

Article	Order No.
① SICCO Mini 1 – Premium desiccator Polycarbonate (PC) enclosures, transparent	10 17 69501
② SICCO Mini 1 – Premium desiccator Protect Polycarbonate (PC) enclosures, orange	10 17 69426
③ SICCO Mini 1 – Premium desiccator Black PMMA enclosures, black, opaque to visible and UV light	10 17 69406
④ SICCO Mini-Desiccator Mobile Premium With practical handle	10 17 61986
⑤ SICCO Mini-Desiccator for Gas Filling Premium Two connections for gas filling including quick couplings with self-sealing valves and hose	10 17 61996

