

Tubing, Deutsch & Neumann

Tubing made of silicone rubber (VMQ), meets the following standards: BFR XV, FDA CFR 21§ 177.2600, EP-Europ. Pharmacopoeia. Test for biocompatibility according to ISO 10993-1, transparent, durometer 60 Shore A, temperature range -60°C to +200°C, short periods up to +260°C.

I.D. mm	O.D. mm	Wall mm	Order No.	PU m/Roll
0.5	2.5	1	27 34 60061	25
1	1.8	0.4	27 34 60003	25
1	3	1	27 34 60004	25
1.5	3.5	1	27 34 60008	25
1.5	4	1.25	27 34 60068	25
2	4	1	27 34 60011	25
2	6	2	27 34 60012	25
3	5	1	27 34 60015	25
3	6	1.5	27 34 60016	25
3	7	2	27 34 60017	25
4	6	1	27 34 60019	25
4	7	1.5	27 34 60020	25
4	8	2	27 34 60021	25
5	7	1	27 34 60023	25
5	8	1.5	27 34 60024	25
5	9	2	27 34 60025	25
5	10	2.5	27 34 60085	25
6	8	1	27 34 60026	25
6	9	1.5	27 34 60027	25
6	10	2	27 34 60028	25
7	10	1.5	27 34 60029	25
7	11	2	27 34 60030	25
8	10	1	27 34 60090	25
8	11	1.5	27 34 60031	25
8	12	2	27 34 60032	25
9	13	2	27 34 60036	25
10	13	1.5	27 34 60037	25
10	14	2	27 34 60038	25
10	16	3	27 34 60040	25
12	16	2	27 34 60042	25

Minimum order quantity 5 meters and in 5-meter-steps!

