

Clamp Holders/Frame Clamps, DIN 12895, BOCHEM

Different screw types:

- Type 1: thumb screw M8/M10
- Type 2: heart screw M6/M8
- Type 3: socket screw M6/M8
- Type 4: safety screw „heart“ type M8
- Type 5: safety screw „thumb“ type M10

Article	Order No.
① Bosshead 18/10 steel, clamping width 16,5 mm, type 2, M6	31 05 05300
Safety bosshead 18/10 steel, clamping width 16,5 mm, same as Fig. 1, type 4, M8	31 05 05305
Bosshead malleable cast iron, chromium plated, clamping width 16,5 mm, type 1, M8	31 05 05360
Bosshead malleable cast iron, chromium plated, clamping width 20 mm, type 1, M8	31 05 05359
Bosshead malleable cast iron, chromium plated, clamping width 36 mm, type 1, M8	31 05 05369
Safety bosshead malleable cast iron, chromium plated, clamping width 16,5 mm, same as Fig. 1, type 4, M8	31 05 05365
② Cross-type bosshead 18/10 steel, clamping width 16,5 mm, type 2, M6	31 05 05301
Safety cross-type bosshead 18/10 steel, clamping width 16,5 mm, same as Fig. 2, type 4, M8	31 05 05306
Cross-type bosshead malleable cast iron, chromium plated, clamping width 16,5 mm, type 1, M8	31 05 05361
Safety cross-type bosshead mall. cast iron, chromium plated, clamp. width 16,5 mm, as Fig. 2, type 4, M8	31 05 05366
③ Bosshead rotatable 18/10 steel, clamping width 16,5 mm, type 2, M6	31 05 05302
Bosshead rotatable malleable cast iron, chromium plated, clamping width 16,5 mm, type 1, M8	31 05 05362
④ Bosshead for grids 18/10 steel, clamping width 13 mm, type 2, M6	31 05 05303
Bosshead for grids malleable cast iron, chromium plated, clamping width 13,5 mm, type 2, M6	31 05 05363
⑤ Hook-type bosshead 18/10 steel, clamping width 13 mm, type 2, M8	31 05 05304
Hook-type bosshead steel, nickel plated, clamping width 13 mm, type 2, M8	31 05 05364
⑥ Bosshead aluminium, clamping width 16,5 mm, type 1, M8	31 05 05332
Safety bosshead aluminium, clamping width 16,5 mm, as Fig. 6, type 4, M8	31 05 05337
⑦ Universal bosshead aluminium, clamping width 13 mm, type 1, M8	31 05 05334
⑧ Cross-type bosshead aluminium alloy, clamping width 16,5 mm, type 1, M8	31 05 05350
Safety cross-type bosshead aluminium alloy, clamping width 16,5 mm, as Fig. 8, type 4, M8	31 05 05356
Cross-type bosshead aluminium alloy, clamping width 27 mm, type 1, M10	31 05 05352
Safety cross-type bosshead aluminium alloy, clamping width 27 mm, as Fig. 8, type 5, M10	31 05 05357
⑨ Safety screw M8 made of stainless steel, with rotatable steel button, type 4, length 65 mm	10 05 55250



WWQ7J008

