

## Graduated Pipettes, Hirschmann

**Pipettes graduated to the tip**, tolerances better than Class B, short line graduation, AR-GLAS®, clear glass, acc. to DIN EN ISO 835, type 3, graduation and markings in durable amber stain. EX calibrated. For 5 ml and up, equipped with cotton wool stopper as a standard.

| Vol.            | Graduation | Flow<br>time<br>s | Tol. ± | Order No.          | PU<br>pc/Pack |
|-----------------|------------|-------------------|--------|--------------------|---------------|
| ml              | ml         |                   | ml     |                    |               |
| 0.5             | 0.01       | 2 – 11            | 0.0075 | <b>14 71 11121</b> | 12            |
| 1               | 0.01       | 2 – 11            | 0.010  | <b>14 71 11127</b> | 12            |
| 1               | 0.1        | 2 – 11            | 0.010  | <b>14 71 11129</b> | 12            |
| 2 <sup>1)</sup> | 0.01       | 2 – 11            | 0.015  | <b>14 71 11134</b> | 12            |
| 2               | 0.02       | 2 – 11            | 0.015  | <b>14 71 11135</b> | 12            |
| 2               | 0.1        | 2 – 11            | 0.015  | <b>14 71 11137</b> | 12            |
| 5               | 0.05       | 5 – 14            | 0.045  | <b>14 71 11148</b> | 12            |
| 5               | 0.1        | 5 – 14            | 0.045  | <b>14 71 11149</b> | 12            |
| 10              | 0.1        | 5 – 17            | 0.075  | <b>14 71 11158</b> | 12            |
| 20              | 0.1        | 9 – 21            | 0.150  | <b>14 71 11163</b> | 6             |
| 25              | 0.1        | 9 – 21            | 0.150  | <b>14 71 11166</b> | 6             |

<sup>1)</sup> In addition to DIN size



**HIRSCHMANN®**  
 **WW4ZV003**

