

The constant climate chamber with the unique **ControlCOCKPIT** for quick, intuitive operation. Unparalleled homogeneity of temperature and humidity for long-term stability testing. Designed in particular for testing pharmaceuticals according to ICH, Q1A and Q1B, Option 2, and other comparable standards for stability testing of cosmetics and foods.

For testing according to ICH Q1B, model ICHL / ICHLeco is equipped with an illumination unit.

The model ICH C offers in addition to the standard equipment of the ICH / ICHeco a digitalized electronic CO₂ control with a setting range of 0 to 20% CO₂ (ICH750: 0 to 10% CO₂).

With TwinDISPLAY (a detailed description of the model variant can be found on page XXX).

Technical data:

Power supply: 230 V, 50/60 Hz

Operating temperature range ICH/ICHeco/
ICHL/ICHLeco with humidity and/or light:

+10°C to +60°C

Operating temperature range ICH C with

and without humidity:

+10°C to +50°C

Operating temperature range without humidity ICH/ICHeco:

-10°C to +60°C

(not suitable for permanent storage at minus temperatures. In case of permanent operation, icing of the glass door may occur)

Operating temperature range without humidity ICHL / ICHLeco:

0°C to +60°C

Setting temperature range ICH/ICHeco:

-10°C to +60°C

Setting temperature range ICHL/ICHLeco:

0°C to +60°C

Setting temperature range ICH C:

+10°C to +50°C

Humidity range:

10 to 80 % rh



Type	Outer dimensions W x H x D mm	Inner dimensions W x H x D mm	Vol. approx. l	Wght approx. kg	P rating approx. W	Order No.
ICH110	745x1233x585	560x480x400	108	109	1350	10 26 00110
ICH260	824x1552x685	640x800x500	256	160	1350	10 26 00260
① ICH750	1224x1950x785	1040x1200x600	749	249	1350	10 26 00750
ICH110eco	745x1233x585	560x480x400	108	114	1350	10 26 00111
ICH260eco	824x1552x685	640x800x500	256	165	1350	10 26 00261
ICH750eco	1224x1950x785	1040x1200x600	749	254	1350	10 26 00751
ICH110L	745x1233x585	560x480x400	108	109	1450	10 26 01110
ICH260L	824x1552x685	640x800x500	256	160	1450	10 26 01260
ICH750L	1224x1950x785	1040x1200x600	749	249	1530	10 26 01750
ICH110Leco	745x1233x585	560x480x400	108	114	1450	10 26 00112
ICH260Leco	824x1552x685	640x800x500	256	165	1450	10 26 00262
ICH750Leco	1224x1950x785	1040x1200x600	749	254	1530	10 26 00752
ICH110C	745x1233x585	560x480x400	108	109	1350	10 26 02110
ICH260C	824x1552x685	640x800x500	256	160	1350	10 26 02260
ICH750C	1224x1950x785	1040x1200x600	749	249	1350	10 26 02750

External dimensions: Depth without door handle, depth of door handle 56 mm

Inner dimensions: Depth is reduced by 33 mm for the fan.

Accessories:

For additional stainless steel grids and stainless steel perforated plates, refer to ICP models.

An extensive selection of accessories and options is available on request.

We reserve the right of technical modifications. Dimensions are subject to confirmation.

All performance characteristics are typical mean values for serial units.