

Tandem Heaters, Gestigkeit

Hotplates are made of smoothly finished cast-iron with central expansion recesses. Overflow edge and cover hood are made of rust-proof stainless steel. Each unit has a screw-in fitting for a supporting retort rod. Designed for a maximum temperature of 400°C, infinitely variable from 10 to 100%. 2 pilot lamps, 230 V AC, 100% duty cycle. Models SGR... can be controlled in addition by a contact thermometer. The customary electronic K thermometers can be attached also directly.

Tandem heaters without relay, plate dia. 150 mm

Type	Quantity heating plates	Outer W × H × D mm	P rating W	Wght kg	Order No.
SG 1	1	175×160×200	500	2.7	43 06 10681
SG 2	2	300×160×200	1000	5.4	43 06 10682
SG 3	3	525×160×200	1500	8.1	43 06 10683
SG 4	4	700×160×200	2000	10.8	43 06 10684
SG 5	5	875×160×200	2500	13.5	43 06 10685
SG 6	6	1050×160×200	3000	16.2	43 06 10686

Tandem heaters without relay, plate dia. 85 mm

Type	Quantity heating plates	Outer W × H × D mm	P rating W	Wght kg	Order No.
① SGK 1	1	125×145×155	450	1.5	43 06 10688
SGK 4	4	485×145×155	1800	4.8	43 06 10689
SGK 6	6	725×145×155	2700	7.0	43 06 10690

Tandem heaters with relay and contactor bushing, plate dia. 150 mm

Type	Quantity heating plates	Outer W × H × D mm	P rating W	Wght kg	Order No.
SGR 1	1	175×160×200	500	3.0	43 06 10691
SGR 2	2	350×160×200	1000	6.0	43 06 10692
② SGR 3	3	525×160×200	1500	9.0	43 06 10693
SGR 4	4	700×160×200	2000	12.0	43 06 10694
SGR 5	5	875×160×200	2500	15.0	43 06 10695
SGR 6	6	1050×160×200	3000	18.0	43 06 10696

Accessories

Article	Use	Order No.
Stainless steel support rod ST 12, screw-on, 12 mm Ø		44 06 48001
Holder HK3	for contact thermometer	44 06 48015
Silicone cable SK 83 with 3-pole connector	for contact thermometer	44 06 48016

