

Hot Plates, Gestigkeit

Electrical hot plates with variable temperature control, with or without a thermostatic regulator. Robust construction for continuous performance. Aluminium alloy hotplate. Asymmetrical heating system (hotplate corners and edges are subjected to more heat) ensure an even temperature over the entire heating surface. Asbestos-free insulation. The housing is constructed from high-grade, stainless steel No. 1.4301, whereby the central section has been additionally sprayed in orange. Four adjustable feet ensure extra stability. Connecting cable 1,75 m. long. At 230 V~ up to 3200 W with earthing pin plug.

Hot plates with infinitely variable control

Type	A	B	C	D	P rating	Voltage	Temp.	Wght	Order No.
	mm	mm	mm	mm	W	V	°C	kg	
HD0	300	300	312	312	1800	230	370	10	43 06 00120
HD1	350	350	358	358	2200	230	370	12	43 06 00121
HE1	290	440	308	458	2400	230	370	14	43 06 00131
HD2	350	500	364	514	2850	230	370	19	43 06 00122
HD3-230	430	580	442	592	4000	230	370	25	43 06 00123
HD3-400	430	580	442	592	4000	3×400	370	25	43 06 00140

Hot plates with thermostatic control and power controller from 10 to 100 W-%

Type	A	B	C	D	P rating	Voltage	Temp.	Wght	Order No.
	mm	mm	mm	mm	W	V	°C	kg	
HT01	300	300	312	312	1000	230	30 – 110	11	43 06 01101
① HT02	300	300	312	312	1800	230	50 – 300	11	43 06 01102
HT03	300	300	312	312	1800	230	100 – 370	11	43 06 01103
HT11	350	350	358	358	1150	230	30 – 110	13	43 06 01111
HT12	350	350	358	358	2200	230	50 – 300	13	43 06 01112
HT13	350	350	358	358	2200	230	100 – 370	13	43 06 01113
TH11	290	440	308	458	1650	230	30 – 110	14	43 06 01211
TH12	290	440	308	458	2400	230	50 – 300	14	43 06 01212
TH13	290	440	308	458	2400	230	100 – 370	14	43 06 01213
HT21	350	500	364	514	1800	230	30 – 110	19	43 06 01121
HT22	350	500	364	514	2850	230	50 – 300	19	43 06 01122
HT23	350	500	364	514	2850	230	100 – 370	19	43 06 01123
HT31	430	580	442	592	2000	230	30 – 110	26	43 06 01131
HT32-230	430	580	442	592	4000	230	50 – 300	26	43 06 01132
HT32-400	430	580	442	592	4000	3×400	50 – 300	26	43 06 01232
HT33-230	430	580	442	592	4000	230	100 – 370	26	43 06 01133
HT33-400	430	580	442	592	4000	3×400	100 – 370	26	43 06 01233

Please note:

The range 30 to 110°C is not suitable for cooking purposes.

