

Water baths

The waterbaths are generally used in the laboratory to maintain the temperature of the samples constant. The waterbaths WB series, thanks to the maximum operating temperature of 99°C, meet the different needs of operators and therefore allow them to be used in numerous applications.

The models WB 22P and WB-40P are equipped with a recirculation pump to ensure a faster and more uniform temperature distribution. All models are equipped with a drain drop.

Technical data:	WB-12	WB-22/WB-22-P	WB-40P
Volume:	12 litres	22 litres	40 litres
Max. temperature/resolution:	+99/0.1°C	+99/0.1°C / +85/0.1°C	+85/0.1°C
Temp. homogeneity at 37°C:	±0.5°C	±0.5°C	±0.5°
Temp. variation at 37°C:	±0.1°C	±0.1°C	±0.2°C
Timer:	99:59/continuous	99:59/continuous	99:59/continuous
Overheat control:	Yes	Yes	Ja
Int. Dimensions (W×H×D):	390 × 220 mm	490 × 290 mm	620 × 380 mm
Min. height with hud closed:	150 mm	150 mm	150 mm
Voltage/Power:	230 V / 900 W	230 V / 1100 W	230 V / 2200 W
Ext. Dimensions (W×H×D):	480 × 375 × 310 mm	680 × 395 × 310 mm	830 × 390 × 460 mm
Maximum capacity:	4 modules	8 modules	16 modules
Weight:	12 kg	18 kg	28 kg
Safety class:	2	2	2



Article	Order No.
① WB-12 Water bath	10 13 76012
WB-22 Water bath	10 13 76022
WB-22-P Water bath	10 13 76023
WB-40P Water bath	10 13 76024

Accessories

Article	Order No.
Rack for tubes Ø 13 mm / 20 positions	10 13 76802
Rack for tubes Ø 18 mm / 20 positions	10 13 76812
Rack for tubes Ø 31 mm / 5 positions	10 13 76822
Rack for tubes Ø 56 mm / 8 positions (biberon)	10 13 76842
Rack for blood bags / 5 positions	10 13 76852

①