

Vario Shakers, Bühler

Small, reliable bench top shakers with special shaking motion.

Technical data:

Max. load: 2 kg (KL 2), 10 kg (TL 10/WS 10)
 External dimensions (WxDxH): 355 x 455 x 195 mm, resp. 355 x 450 x 205 mm
 Supply voltage: 230 V, 50/60 Hz (115 V on request)



WWXRZ002



- | Article | Order No. |
|--|-------------------------------------|
| ① Combination shaker KL 2 | 52 61 61150 |
| "2 in 1" unit that can be switched over at any time from orbital to reciprocal motion. | |
| Shaking area: | 300 x 300 mm |
| Speed: | 30 – 420/min infinitely variable |
| Shaking amplitude: | 8 mm |
| Timer: | 0 – 120 min or continuous operation |
| Basic unit includes: | |
| Tray with 3 clamping rails and rubber mat | |

- | Article | Order No. |
|---|-------------------------------------|
| ② Rocking shaker WS 10 | 52 61 61140 |
| Rocking shaker with slow, linear up-and-down motion. | |
| Shaking area: | 340 x 340 mm |
| Speed: | 1 – 23/min infinitely variable |
| Rocking angle: | 5° fixed |
| Timer: | 0 – 120 min or continuous operation |
| Basic unit includes: | |
| Rocking plate with rubber mat. | |
| Multi-level rack with 2 additional trays available as an accessory. | |

- | Article | Order No. |
|--|--------------------|
| Three-dimensional orbital shaker TL 10 | 52 61 61170 |
| Same as WS 10, but with slow three-dimensional orbital motion. | |
| Level inclination gyrating motion can be adjustable from 0° to 9°. | |



①



②

