

## Laboratory Balances GX/GF-A Series, A&D Instruments



- Solid metal housing, sturdy design
- Internal compressor-controlled calibration at the push of a button (GX-A)
- Robust overload protection
- Overload detection and indication
- Backlit LCD display
- Adjustable response characteristics
- Automatic calibration in case of temperature change, interval or push of a button
- RS-232 and USB interface Standard, optional Ethernet interface
- Precision test function with determination of the standard deviation via ECL technology (electronic controlled load)
- Minimum weight computation and optical alarm if actual weight is below minimum
- Flow rate display (FRD) and flow rate comparator
- Two-stage access control and button lock
- Up to 10 user profiles
- Memory for 200 weighing results, 50 calibration results, 50 unit masses
- Tare memory
- Several weighing units, g ,oz , lb, lb-oz, zt, ct, mom, dwt, pcs and SG (specific weight)
- Statistics and comparator function
- Density determination
- Animal weighing program
- Underfloor weighing
- Auto Power ON, Auto Power OFF function
- Capacity indication



### Models with internal calibration

Model	Capacity g	Increment g	Platform mm	Order No.
GX-203A	220	0.001	128 × 128	10 45 72030
GX-303A	320	0.001	128 × 128	10 45 73030
GX-403A	420	0.001	128 × 128	10 45 74030
GX-603A	620	0.001	128 × 128	10 45 76030
GX-1003A	1100	0.001	128 × 128	10 45 71003
① GX-1603A	1620	0.001	128 × 128	10 45 71603
GX-2002A	2200	0.01	165 × 165	10 45 72002
GX-3002A	3200	0.01	165 × 165	10 45 73003
GX-4002A	4200	0.01	165 × 165	10 45 74003
GX-6002A	6200	0.01	165 × 165	10 45 76002
GX-10002A	10200	0.01	165 × 165	10 45 71002
GX-6001A	6200	0.1	165 × 165	10 45 76001
GX-10001A	10200	0.1	165 × 165	10 45 71001

### Models with external calibration

Model	Capacity g	Increment g	Platform mm	Order No.
GF-123A	120	0.001	128 × 128	10 45 70123
GF-203A	220	0.001	128 × 128	10 45 70203
GF-303A	320	0.001	128 × 128	10 45 70303
GF-403A	420	0.001	128 × 128	10 45 70403
GF-603A	620	0.001	128 × 128	10 45 70603
GF-1003A	1100	0.001	128 × 128	10 45 71013
GF-1603A	1620	0.001	128 × 128	10 45 71604
GF-1202A	1200	0.01	165 × 165	10 45 71202
GF-2002A	2200	0.01	165 × 165	10 45 72003
GF-3002A	3200	0.01	165 × 165	10 45 73002
GF-4002A	4200	0.01	165 × 165	10 45 74002
GF-6002A	6200	0.01	165 × 165	10 45 76012
GF-10002A	10200	0.001	165 × 165	10 45 71012
GF-6001A	6200	0.1	165 × 165	10 45 76011
GF-10001A	10200	0.1	165 × 165	10 45 71011



## Accessories

Article	Order No.
<b>GXA-03 Second RS-232C interface</b>	<b>10 45 73232</b>
<b>GXA-04 Comparator output/buzzer/external key entry</b>	<b>10 45 70004</b>
<b>GXA-06 Analogue output</b>	<b>10 45 70006</b>
<b>FXi-08 Ethernet output</b>	<b>10 45 70008</b>
<b>GXA-09 Rechargeable battery pack</b>	<b>10 45 70009</b>
Installed in the factory/at the dealer's	
<b>GXA-10 Large breeze break, made of glass</b>	<b>10 45 70010</b>
<b>GXA-12 Animal weighing pan</b>	<b>10 45 70012</b>
for models with capacity 320 g and up	
<b>GXA-13 Density measurement kit</b>	<b>10 45 70013</b>
only for 1 mg models	
<b>GXA-17 Large breeze break with ionizer</b>	<b>10 45 70017</b>
<b>GXA-23-PRINT External key entry -PRINT with the AX-SW137-PRINT foot switch</b>	<b>10 45 72313</b>
<b>GXA-23-REZERO External key entry with the AX-SW137-REZERO foot switch</b>	<b>10 45 73127</b>
<b>GXA-23-PLUG External key entry with AX-T-314A-S plug</b>	<b>10 45 72314</b>
<b>GXA-24 USB host interface</b>	<b>10 45 70024</b>
Installed in the factory/at the dealer's	
<b>GXA-25 Fanless ionizer</b>	<b>10 45 70025</b>
Static Eliminator	
<b>GXA-26 External IR button</b>	<b>10 45 70026</b>
<b>AX-GXA-31 Display working covers, 5 pcs.</b>	<b>10 45 73105</b>
<b>AX-SW137-PRINT Foot switch for printing function</b>	<b>10 45 70137</b>
<b>AX-SW137-REZERO Foot switch for RE-ZERO function</b>	<b>10 45 71137</b>

