

ASTM Thermometers ACCU-SAFE, Ludwig Schneider



WWZT7004



LUDWIG
SCHNEIDER

- Highly precise lab thermometer „Made in Germany“, solid-stem type, capillary form: white back
- With individual serial number
- Also available in °F
- Standard calibration (WPS and DAkkS) with 3 test points, additional test points available on request

ASTM-Thermometers – ACCU-SAFE – with blue, environmental safety filling, calibrateable

ASTM number	Measuring range °C	Scale °C	Overall length mm	Immersion depth mm	with certificate of conformity Order No.	with factory test certificate Order No.	with DAkkS calibration certificate Order No.
S5C	-38 – +50	1	260	108	10 16 54005	10 16 53105	10 16 53405
S12C	-20 – +102	0.2	435	total	10 16 54012	10 16 53112	10 16 53412
S15C	-2 – +80	0.2	415	total	10 16 54015	10 16 53115	10 16 53415
S18C	+34 – +42	0.1	300	total	10 16 54018	10 16 53116	10 16 53416
S22C	+95 – +103	0.1	300	total	10 16 54022	10 16 53122	10 16 53422
S56C	+19 – +35	0.02	610	total	10 16 54056	10 16 53156	10 16 53456
S58C	-34 – +49	0.5	300	total	10 16 54058	10 16 53158	10 16 53458
S59C	-18 – +82	0.5	300	total	10 16 54059	10 16 53159	10 16 53459
S62C	-38 – +2	0.1	401	total	10 16 54062	10 16 53162	10 16 53462
S63C	-8 – +32	0.1	401	total	10 16 54063	10 16 53163	10 16 53463
S64C	+25 – +55	0.1	401	total	10 16 54064	10 16 53164	10 16 53464
S65C	+50 – +80	0.1	401	total	10 16 54065	10 16 53165	10 16 53465
S66C	+75 – +105	0.1	401	total	10 16 54066	10 16 53166	10 16 53466
S67C	+95 – +155	0.2	401	total	10 16 54067	10 16 53167	10 16 53467
S91C	+20 – +50	0.1	390	76	10 16 54091	10 16 53191	10 16 53491
S116C	+18.9 – +25.1	0.01	615	total	10 16 54116	10 16 53216	10 16 53516
S117C	+23.9 – +30.1	0.01	615	total	10 16 54117	10 16 53217	10 16 53517
S120C	+38.6 – +41.4	0.05	300	total	10 16 54120	10 16 53220	10 16 53520
S130C	-7 – +105	0.5	300	total	10 16 54130	10 16 53230	10 16 53530

