

Pocket pH Meters, WTW®



Pocket pH meters ProfiLine

Field-tested, adapted to the respective applications and the user's requirements: The ProfiLine single parameter devices and sets by WTW®. The Special silicone keypad with tactile feedback is particularly operator-friendly and can be cleaned easily under running water. Can be used with disposable or rechargeable battery for more flexible and economical operation. With backlit graphic display (model 3310 and up) for easy navigation.

Simple and functional: pH 3110

pH 3110: a simple, rugged and waterproof device for portable pH measurement. With built-in calibration timer and 3-point calibration. Large LCD display. Automatic AutoRead function for reproducible measured values.

Technical data pH 3110:

	all values ± 1 digit
pH:	-2.0 to 20.0 ± 0.1 pH -2.00 to 20.00 ± 0.01 pH -2.000 to 19.999 ± 0.005 pH
mV:	$\pm(1200.0 \pm 0.3)$ mV $\pm(2000 \pm 1)$ mV
Temperature:	-5.0 to 105.0°C ± 0.1 °C

Article	Order No.
① pH 3110 single device	10 81 23110
pH 3110 SET 2	10 81 23112
in a case with pH electrode SenTix® 41 and accessories	

pH meter with data logger qualities: pH 3310

Intended for demanding field data collection tasks and recording of extensive arrays. The units have a large memory for 5000 GLP compliant data and an interval-controlled data logger. The plain text menu in four languages provides configuration, operation and calibration (1 to 5 points). Up to 10 calibration logs can be called up to follow up the stability of the connected sensor. With state-of-the-art mini USB interface for communication with the PC.

One of the highlights is CMC, the continuous measurement control: A graphic scale in the display shows whether you are in the confidence range of the calibration points.

Technical data pH 3310:

	all values ± 1 digit
pH:	-2.0 to 20.0 ± 0.1 pH -2.00 to 20.00 ± 0.01 pH -2.000 to 19.999 ± 0.005 pH
mV:	$\pm(1200.0 \pm 0.3)$ mV $\pm(2500 \pm 1)$ mV
Temperature:	-5.0 to 105.0°C ± 0.1 °C

Article	Order No.
② pH 3310 single device	10 81 23310
pH 3310 SET 2	10 81 23312
in a case with pH electrode SenTix® 41 and accessories	

Accessories

Article	Order No.
Protective casing SM Pro	10 81 22780
Shock-absorbent, elastic rubber	

