

Safety Cabinets, asecos

Acid and alkali cabinets with interior fittings

Safe and proper storage of aggressive hazardous material. GS-approved, laboratory furniture standard EN 14727. Body made of epoxy resin-coated steel sheet RAL 7035 (light grey), interior made of highly resistant melamine resin-coated special material plates. Circumferential synthetic lip seals prevent noxious fumes from escaping. Two hermetically separated storage compartments, vented separately. Door opening angle more than 90°. Corrosion-resistant, metal-free air channels. Interior largely freely of metal. Shelves: with removable, liquid-proof and highly resistant plastic trays with general buildings supervisory approval (DIBt).

Model SL.196.120.MV

- 2 folding doors (vertical partition)
- Outside dimensions (W × D × H) mm: ca. 1197 × 603 × 1965

Article	Order No.
① Model SL.196.120.MV (without interior)	10 13 19120
Delivery costs depending on place of delivery	

Model SL.196.060.MH

- 2 folding doors (horizontal partition)
- Outside dimensions (W × D × H) mm: ca. 597 × 603 × 1965

Article	Order No.
② Model SL.196.060.MH (without interior)	10 13 19060
Delivery costs depending on place of delivery	

Interior equipment packages

Recommended configuration: 12 tray pull-outs (SL.196.120.MV), 6 tray pull-outs (SL.196.060.MH)

Article	Width model mm	Width × Depth × Height mm	Order No.
8 tray pull-outs	1200	407 × 468 × 80 (each drawer)	10 13 13607
③ 12 tray pull-outs	1200	407 × 468 × 80 (each drawer)	10 13 13608
4 tray pull-outs	600	407 × 468 × 80 (each drawer)	10 13 13614
④ 6 tray pull-outs	600	407 × 468 × 80 (each drawer)	10 13 13615

Typ 90 fire resistant gas cylinder cabinet

Gas cylinder cabinets for proper storage, provision, and removal of gas cylinders in work rooms pursuant to TRGS 510 and TRBS 3145.

Type-tested fire resistance for a period of 90 minutes pursuant to DIN EN 14470-2 (G90), GS approved. Fire protection insulation with intumescent joint seals. Body made of plastic-coated sheet steel in RAL 7035 (light grey), interior surfaces coated with impact- and scratch-proof synthetics highly resistant to chemicals.

Serial equipment:

- 2 folding doors
- Door opening angle max. 180°
- Profile cylinder lock (chamber can be integrated in available locking systems)
- Adjustment aids to balance floor bumps
- Earth connection
- Integrated air ducts ready for connection (NW 75) to a technical exhaust system
- Options for pipeline ducts through the cabinet ceiling.

Article	Storage capacity gas cylinders	Order No.
⑤ G90.205.120 (without interior)	4 × 50 l	10 13 15120

Compressed gas cylinder cabinet also available in widths of 600 mm, 900 mm and 1400 mm.

Delivery costs depending on place of delivery.

Interior equipment version model G90.205.120

Interior fitting consists of:

- Roll-in flap
- Cylinder holder with 4 tension belts
- Mounting rails

Article	Order No.
⑥ Interior equipment	10 13 13775



① ③



② ④



⑤ ⑥